



Linetex[®]

OUTDOOR | MARINE | AUTOMOTIVE






























SPRADLING[®]
For the long run

Colour Palette

28 inspiring colours



LNT-1651
FRAPPE

 LNT-3000 BOND	 LNT-3460 BAMBOO	 LNT-5194 BUTTER	 LNT-7893 ROCK	 LNT- 2888 DUST	 LNT- 6528 NUT	 LNT-8288 CHESTNUT
 LNT-6027 TOAST	 LNT-7686 CACAO	 LNT-1323 TRUFFLE	 LNT-9503 MINT	 LNT-1941 EMERALD	 LNT-4437 MATCHA	 LNT-2154 TEJA
 LNT-4571 WAVE	 LNT-6480 SPHERE	 LNT-4233 ICELAND	 LNT-4031 ATITLAN	 LNT-8215 SHALLOW	 LNT-4030 MILOS	 LNT-9502 CHALK
 LNT-4768 GLACIER	 LNT-5024 BASSALT	 LNT-2403 MIST	 LNT-8577 IRON	 LNT-1340 CLIFF	 LNT-4210 SHALE	

Technical data sheet

Composition:	Topcoat: Vinyl
Backing:	Backing 100% Polyester
Weight:	635 gr/m ²
Width:	min. 137cm
Roll size:	+/- 30m*
Abrasion:	> 100.000 cycles (MARTINDALE)
Cold Crack:	-29° C
UV-Resistance:	ISO 105 B02: ≥7/8 (Blue Wool Scale) ISO 105 B04: ≥4/5 (Grey Scale)

* Typical roll length. Length may vary depending on the availability of standard roll size

Flame Retardancy**:	EU EN 1021 Part 1 & 2 EU IMO 2010 FTP Part 8 DE DIN 4102 B2 US FMVSS302 US UFAC Fabric - Class I US NFPA 260 Class I
Other characteristics	EU (MED) Marine Equipment Directive UK UKCA

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behaviour of this or any other material under actual conditions.

FINISHES AND TREATMENTS



Antimicrobial:	Waterproof Mildew Resistant Backing and Face Antifungal Protection Antibacterial Protection Antimycotic Protection
-----------------------	--

*** Testing was conducted with material exposed to Staphylococcus aureus, Staphylococcus aureus (MRSA), Escherichia coli and Klebsiella pneumoniae.

WARRANTY 5 Years. Terms and Conditions apply.

PERMABLOK³ and SPRADLING[®], are registered trademarks of Spradling Holdings, Inc[®].




SUSTAINABLE PRODUCT PROFILE

Attributes

PHTHALATE FREE

Heavy Metal Free



*In accordance with REACH, RoHs and ECHA regulations

- AZO = Azo dyes
- CFC = Chlorofluorocarbons
- HCFC = Hydrochlorofluorocarbons
- BPA = Bisphenol A
- PBTs = Persistent Bio accumulative and Toxic Chemicals
- PCP = Pentachlorophenol
- PCB = Pentachlorinated Biphenyl
- PCT = Polychlorinated Terphenyls

Certifications



Sustainable manufacturing certifications



Compliances



SPRADLING[®]
For the long run

WWW.SPRADLING.EU